

TECHNICAL DATA

Scapa 3163

Waterproof Cloth Tape

DESCRIPTION

Scapa 3163 is a superior grade utility polyethylene laminated waterproof cloth tape, coated with a pressure sensitive adhesive.

Scapa 3163 is available in black and silver as standard.

APPLICATIONS

- Sealing, bundling, masking, holding and protection applications
- General purpose maintenance and repair
- Medium temperature duct sealing
- Carpet joining and edging
- Double glazing unit sealing

PRODUCT BENEFITS

- Superior utility grade cloth tape
- Improved abrasion resistance on standard economy cloth tape
- Attractive gloss appearance
- Good resilient finish
- Very versatile, can be used for a vast range of applications
- Excellent initial adhesion
- Easy tear and good unwind
- Easy to use in application no twist or curl
- Flexible and conformable

lssue: 3 Date: 28/06/10 Page 1 of 2 3163.doc

www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.

TECHNICAL PROPERTIES

	Unit	Nominal Value	Test Method
Thickness	mm	0.23	AFERA 5006*
Tensile Strength	N/cm	40	ICE454-2
Adhesion to Steel	N/cm	5	ICE454-2
Adhesion to Backing	N/cm	3	ICE454-2
Service Temperature	°C	-20 - 75	

^{*}Scapa Internal Test Method to measure thickness now replaced by the more rigorous AFERA method.

STANDARD PRESENTATION

Roll Length: 50m

Roll Width: 25mm, 50mm, 75mm,Core: 76mm Cardboard

Packaging: Bulk packed with interleaving between layers or shrink wrapped in packs of 4 *

Note: Information on stock items, non-standard sizes, and lead times is available on request

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Shelf life will vary with conditions of use and is affected by climatic environment, but should not be less than two years from date of manufacture, if stored in a moderate climate and good conditions.

Issue: 3 Date: 28/06/10 Page 2 of 2 3163.doc

www.scapa.com

^{*} Dependant on size / colour combination